

Custom Logs

Overview

Send log messages with customized severity levels, extra data and/or custom labels. Use `CoralogixLogSeverity` to define severity levels for logs in the Coralogix system.

NOTE

You can pass any `key:value` to the extra data object.

Case	Raw value	Severity level
<code>debug</code>	1	Debug
<code>verbose</code>	2	Verbose
<code>info</code>	3	Informational
<code>warn</code>	4	Warning
<code>error</code>	5	Error
<code>critical</code>	6	Critical

Examples

Custom severity level

```
CoralogixRum.log(  
  CoralogixLogSeverity.Error,  
  "Custom log message error"  
)
```

Custom severity level, extra data

```
CoralogixRum.log(  
  CoralogixLogSeverity.Error, 'this is an error custom log with extra  
data', { data: 'tbd' });
```

```
)
```

Direct severity level call, extra data

```
CoralogixRum.error('this is a custom log with error severity', { data: 'tbd' });  
)
```

Custom log, extra data and label

```
CoralogixRum.warning(  
  'this is a custom log message with warning severity',  
  {  
    data: 'tbd',  
  },  
  {  
    my_label_key: 'my label value',  
  }  
);
```

Custom severity level, optional extra data (unless label is provided)

The extra data is optional unless labels are specified. If labels are present, extra data becomes required, though it may be set to `null` if no data is available.

```
CoralogixRum.log(CoralogixLogSeverity.Info, 'this is a custom log message with info severity', null, {  
  my_label_key: 'my label value',  
});
```

🕒 Last updated: April 15, 2025

Was this helpful?

Leave your feedback here.

☐ Yes ☐ No

Send

© 2025 Coralogix. All rights reserved.

Generated on: November 17, 2025

Source: <https://coralogix.com/docs/user-guides/rum/sdk-features/custom-logs/>